



TECHNICAL DATA SHEET

Date: 13.02.2018, Version: 8

Range name :

SICURA LOW NRGY/LED - Bases

Description :

SICURA LOW NRGY/LED is a high reactivity free radical system especially developed for UV sheetfed presses equipped with the low energy UV technology and/or LED dryer (wavelength output : 385-395 nm). Range of concentrated base for blending realization.

Application Fields / Market :

All types of commercial printing jobs in sheetfed UV application.
The use for packaging applications is also possible depending on the substrate and on the drying equipment of the press.

Product safety:

This series is not suitable for Food packaging and not suitable for primary packaging for pharma or hygiene.
In case of food packaging or primary packaging for pharma and hygiene application, please contact our technical department.
For further information, please refer to Siegwirk's Customer Guidance: printing Inks for Food Packaging ("Know-How") on: <https://www.siegwerk.com/en/our-responsibility/product-responsibility/customer-communications/food-packaging-safety.html>

Substrates:

All types of papers & plain boards
Adhesion on non-absorbent substrates and other resistances properties require to be primarily checked for each new application

Features - Performances:

- ⇒ **ON THE PRESS SIDE**
 - Exceptional stability of ink / water balance
 - Compatibility with all types of dampening systems using either alcohol minimizer or conventional water fountain solutions
 - Inks remain very stable on the rollers
 - No misting even on high speed presses
 - Very high reactivity
Reactivity is influenced by the substrate, efficiency of the lamps and reflectors, the thickness of the ink layer, colours and superposition, etc...
 - Compatible with mix rollers
- ⇒ **ON THE PRINTING SIDE**
 - High colour strength
 - High gloss level
 - Excellent flexibility for folding and creasing finishing operations
 - Excellent rub resistance
 - Over printable with Sicura Flex OPV or Offset OPV suitable for the type of dryer installed on the press. For a more appropriate offer please consult our technical department



The range :

Colours	Reference numbers	IWS (1)	Alcohol	Solvent	Alkali	Laser or UV varnishing
Low NRGY/LED Fast Yellow	71-300756-5	7	5	4	5	Yes
Low NRGY/LED Yellow	70-300757-3	5	5	5	5	Yes
Low NRGY/LED Orange 021	71-700411-3	5	5	5	5	Yes
Low NRGY/LED Warm Red	71-801713-0	5	4	3	5	Yes
Low NRGY/LED Red 032	71-801712-2	6	4	4	5	Yes
Low NRGY/LED Rubine Red	71-801710-6	5	5	5	3	Yes
Low NRGY/LED Fast Magenta	70-801709-0	6	5	5	5	Yes
Low NRGY/LED Fast Rhodamine Red	71-801711-4	7	5	5	5	Yes
Low NRGY/LED Fast Purple	71-100394-7	7	5	5	5	Yes
Low NRGY/LED Fast Violet	71-100395-4	7	5	5	5	Yes
Low NRGY/LED Fast Blue 072	71-120534-4	7	5	5	5	Yes
Low NRGY/LED Fast Reflex Blue	71-120537-7	7	5	5	5	Yes
Low NRGY/LED Reflex Blue	71-120536-9	3	1	1	1	No
Low NRGY/LED Process Blue	70-120533-8	8	5	5	5	Yes
Low NRGY/LED Green	71-500914-8	8	5	5	5	Yes
Low NRGY/LED Neutral Black	71-900608-2	7	5	5	5	Yes
Low NRGY/LED Transparent White	71-000293-2	-	5	5	5	Yes
Low NRGY Opaque White	71-010372-2	7	5	5	5	Yes
LED Opaque White	71-010450-6	7	5	5	5	Yes

(1) These light fastness values refer to a solid tone printing. Light fastness decreases when colour strength is reduced or if colours are intermixed

Warning :

- These UV inks are guaranteed for a period of 12 months after manufacture. Please check use by date indicated on the cans.
- UV inks must be stored in a cool place
- Open containers must be kept away from light sources and be closed after usage.
- Please consult material safety data sheets (MSDS) for more information.
- We do not recommend the use of these inks for the printing of posters or other displays/jobs destined to be exposed to outdoor climatic conditions

Auxiliary printing additives :

When certain substrates or machine conditions imply adjustments of the ink properties, the additives should be chosen in function of this substrate and of the further processing of the printed matter.

Role	Designation	Reference numbers	Proportions
Thinner	Thinner	81-470072-0	1 to 3 %
Tack reducer	Anti-tack paste	81-470071-2	1 to 3 %
Cure booster	Photo-initiator	71-470108-3	2 to 5 %
Roller saturator	Roller saturator paste	81-470537-2	Direct on rollers

For Fountain additives and Cleaning products please contact our technical department.



Packing size:			
✓	Vacuum Metallic Tins	2.5 kg	Packaging code 1200

This information is based on our experience and on results obtained in the laboratory, using specific processes and types of application. In view of the diversity of substrates and printing conditions, this data is communicated for information purposes only and is provided without any warranty on our part and must be authenticated by industrial tests before the products are used. Improvements are being made to our products on an ongoing basis and we therefore reserve the right to modify their composition as well as the contents of our technical data sheets. We disclaim any liability for applications for which this ink series is not foreseen.

Siegwerk Druckfarben AG & Co. KGaA

Siegwerk France - 13 Route de Taninges – BP506 74105 Annemasse cedex, www.siegwerk.com